

ISCS - Bug #770

line3# PIS fas pis

09/07/2020 03:33 PM - lq Du

| | | | |
|-----------------|----------|-----------------|------------|
| Status: | Resolved | Start date: | 09/07/2020 |
| Priority: | High | Due date: | |
| Assignee: | lq Du | % Done: | 0% |
| Category: | | Estimated time: | 0.00 hour |
| Target version: | | Spent time: | 0.00 hour |

Description

- 48. PIS 联动 void pis (int RtuNo, int Mode, int Func, int Val, char *pMsg)

参数说明:

RtuNo: RTU 号

Mode: 模式 1 紧急模式 2 正常模式

Func: 功能选择: 1 Volume 有效; 2: 开/关机; 3: MsgId 有效; 4:自定义信息有效

Val: 功能值

1 音量设置: 0-255:

2 开关机:0 关机, 1 开机;

3 信息号:1-1024:

4 自定义信息: 无定义

pMsg: Func=4 时有效——PIS 面板显示内容

返回值: 无

Hex dump line 1

Hex dump line 2

Hex dump lines 3-10 showing memory addresses and values, including '5C 00 5C 00' at the end.

Hex dump line 11

Hex dump lines 12-19 showing memory addresses and values, including '3F 00' repeated.

